



A multi-temperatures cabinet with a temperature staggering from 6°C to 20°C to serve your wines in the best possible conditions.



EAN Code : 3543290003407

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	10	141
Mixed Configuration	2	1	177
Minimum Configuration (100% storage)	3	0	182
Standard Configuration	4	-	177

UNIVERSAL SHELF

Universal shelf : AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level : 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



« Storage »
72 Bottles



« Sliding »
12 Bottles



« Presentation »
6 + 36 Bottles

ArteVino AOHUI shelf has a label holder :



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

* Standard configuration

** Traditional Bordeaux bottles

*** Calculated with an ambient temperature of 25°C

**** Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration

***** R600a gas. With a R134a gas (for US, CA, Korea, Taiwan): 38 db(A)

Range :	OXYGEN
Model :	OXMMT177NPD
Fonction :	Service
Capacity* :	177 Bottles**



A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

Gross weight, packaged(kg)*	: 88,4
Net weight (kg)*	: 73,4
Dimensions in packaging H x W x D (mm)	: 1595 x 700 x 750
Dimensions H x W x D(mm)	: 1480 x 680 x 700
Color scheme	: Black

Energy efficiency rating	: A+
Acoustic emissions (dB(A))*****	: 37
Electrical power (W)**	: 70
Electrical intensity (A)**	: 0.33
Consumption per 24h (KWh) ***	: 0.33
Annual energy consumption AEC* (kWh/year) ****	: 121
Ambient temperature operating limit	: 12 - 30°C

- ✓ **Digital electronic controls with temperature setting range from 6°C to 10°C (lower cabinet area) and 15°C to 20°C (upper cabinet area)**
- ✓ **Temperature display on indoor sidewall**
- ✓ **Double Hot/ Cold circuit > Automatic « Winter function »**
- ✓ **Temperature fault alarm icon**
- ✓ **Interior lining of dimpled aluminium**
- ✓ **Solid door**
- ✓ **Hygrometry ensured by the principle of thermodynamic pump**
- ✓ **2 adjustable feet**
- ✓ **Lock**
- ✓ **Storage grid in the low part**
- ✓ **Inox Handle**