





6074V

| Range : | 6000 Series | | | | |
|------------|---|--|--|--|--|
| Function : | Single-Temperature Maturing or Service | | | | |
| Pack: | Premium | | | | |
| Capacity: | 74 Bottles** | | | | |

GENERAL FEATURES

| | Full Glass door | Glass door | Solid door | |
|--|---------------------|---------------------|------------|--|
| Gross weight packaged / net weight (kg)* | 72,5 / 60 70,5 / 58 | | 68,5 / 56 | |
| Permitted ambient temperature range | 0 – 30°C | 0 – 35°C / 0 – 95°F | | |
| Dimensions unpackaged H x W x D (mm) | 960 × 680 × 690 | | | |
| Dimensions packaged H x W x D (mm) | 1090 x 720 x 760 | | | |
| Colour of body | Nero | | | |

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 20°C
- LED screen with touch buttons
- Electronic inner display and settings digital screen
- Hygrometry and temperature visualisation
- Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production : • Air fan

• Compressor R600a/R134a Cords : • CE/UK/JA/AU/CH/CN/US

Hot production: • Heating element

Hot release: • Automatic

• Threshold : adjustable

Inner material : • Aluminium

Exterior coating material : • HDF (High Density Fiber)
Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors : Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- Charcoal filter (with meter)
- Humidity cassette
- Front adjustable feet
- Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Premium Pack: 5 sliding shelves ACMS

Capacity: 74 bottles**



OPTIONS PLUS



Lighting Warranty
Atmosphere

A

lighting





Equiped with a brake wood or glossy black f

Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

| Wiring | 230V-50Hz | | | 115V-60Hz | | |
|--|-----------|-------|------------|-----------|-------|------------|
| Doors type | Solid | Glass | Full Glass | Solid | Glass | Full Glass |
| Energy efficiency rating | A+ | Α | Α | 1 | 1 | 1 |
| Annual energy consumption Aec (kWh/year)*** | 114 | 146 | 146 | 146 | 183 | 183 |
| Acoustic emissions (dB(A)) | 37 | 37 | 37 | 38 | 38 | 38 |









| Range : | 6000 Series | | | |
|------------|---------------------|--|--|--|
| Function : | Single-Temperature | | | |
| | Maturing or Service | | | |
| Pack: | Presentation | | | |
| Capacity: | 70 Bottles** | | | |

GENERAL FEATURES

| | Full Glass door Glass door | | Solid door | |
|--|----------------------------|---------------------|------------|--|
| Gross weight packaged / net weight (kg)* | 72,5 / 60 70,5 / 58 | | 68,5 / 56 | |
| Permitted ambient temperature range | 0 – 30°C | 0 – 35°C / 0 – 95°F | | |
| Dimensions unpackaged н x W x D (mm) | 960 × 680 × 690 | | | |
| Dimensions packaged H x W x D (mm) | 1090 x 720 x 760 | | | |
| Colour of body | Nero | | | |

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 20°C
- LED screen with touch buttons
- Electronic inner display and settings digital screen
- Hygrometry and temperature visualisation
- Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production : • Air fan

 $\begin{array}{ccc} & * \ Compressor \ R600a/R134a \\ Cords: & * \ CE/UK/JA/AU/CH/CN/US \end{array}$

Hot production: • Heating element

Hot release:

• Automatic

• Threshold : adjustable

Inner material : • Aluminium

Exterior coating material : • HDF (High Density Fiber)

Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors : Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- · Charcoal filter (with meter)
- Humidity cassette
- Front adjustable feet
- Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Presentation Pack: I presentation kit AOPRESAR +

2 sliding shelves ACMS Capacity: 70 bottles**







OPTIONS PLUS



Shelves

Equiped with a brake Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

| Wiring | 230V-50Hz | | | 115V-60Hz | | |
|--|-----------|-------|------------|-----------|-------|------------|
| Doors type | Solid | Glass | Full Glass | Solid | Glass | Full Glass |
| Energy efficiency rating | A+ | Α | Α | 1 | 1 | 1 |
| Annual energy consumption Aec (kWh/year)*** | 114 | 146 | 146 | 146 | 183 | 183 |
| Acoustic emissions (dB(A)) | 37 | 37 | 37 | 38 | 38 | 38 |