



6182V



Range :	6000 Series			
Function:	Single-Temperature			
	Maturing or Service			
Pack:	Premium			
Capacity:	182 Bottles**			

GENERAL FEATURES

	Full Glass door Glass door		Solid door	
Gross weight packaged / net weight (kg)*	110 / 94 108 / 92		103 / 87	
Permitted ambient temperature range	0 – 30°C	0 - 35°C / 0 - 95°F		
Dimensions unpackaged H x W x D (mm)	960 × 680 × 690			
Dimensions packaged H x W x D (mm)	1090 x 720 x 760			
Colour of body	Nero			

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 20°C
- LED screen with touch buttons
- Electronic inner display and settings digital screen
- Hygrometry and temperature visualisation
- Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production : • Air fan

 $\begin{array}{ccc} & * \ Compressor \ R600a/R134a \\ Cords: & * \ CE/UK/JA/AU/CH/CN/US \end{array}$

Hot production: • Heating element

Hot release: • Automatic

• Threshold : adjustable Inner material : • Aluminium

Exterior coating material : • HDF (High Density Fiber)

Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors : Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- Charcoal filter (with meter)
- Humidity cassette
- Front adjustable feet
- Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Premium Pack: 14 sliding shelves ACMS

Capacity: 182 bottles**



OPTIONS PLUS



Lighting Warranty
Atmosphere
lighting

A





Shelves

Equiped with a brake Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

Wiring	230V-50Hz			115V-60Hz		
Doors type	Solid	Glass	Full Glass	Solid	Glass	Full Glass
Energy efficiency rating	A+	Α	Α	1	1	/
Annual energy consumption Aec (kWh/year)***	128	165	165	183	256	256
Acoustic emissions (dB(A))	37	37	37	38	38	38





6182V

Range :	6000 Series			
Function :	Single-Temperature Maturing or Service			
	Muturing or Service			
Pack:	Presentation			
Capacity:	I 62 Bottles**			



GENERAL FEATURES

	Full Glass door Glass door		Solid door	
Gross weight packaged / net weight (kg)*	110 / 94 108 / 92		103 / 87	
Permitted ambient temperature range	0 – 30°C	0 - 35°C / 0 - 95°F		
Dimensions unpackaged н x W x D (mm)	1825 x 680 x 690			
Dimensions packaged H x W x D (mm)	1950 × 720 × 760			
Colour of body	Nero			

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 20°C
- · LED screen with touch buttons
- Electronic inner display and settings digital screen
- Hygrometry and temperature visualisation
- Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production : • Air fan

 $\begin{array}{ccc} & * \ Compressor \ R600a/R134a \\ Cords: & * \ CE/UK/JA/AU/CH/CN/US \end{array}$

Hot production: • Heating element

Hot release: • Automatic

• Threshold : adjustable Inner material : • Aluminium

Exterior coating material : • HDF (High Density Fiber)

Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors : Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- · Charcoal filter (with meter)
- Humidity cassette
- Front adjustable feet
- Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Presentation Pack: 2 presentation kits AOPRESAR +

7 sliding shelves ACMS Capacity: 162 bottles**



options PLUS 2

Warranty

extension



Atmosphere lighting







Shelves

Equiped with a brake Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

Wiring	230V-50Hz			115V-60Hz		
Doors type	Solid	Glass	Full Glass	Solid	Glass	Full Glass
Energy efficiency rating	A+	Α	Α	1	1	1
Annual energy consumption Aec (kWh/year)***	128	165	165	183	256	256
Acoustic emissions (dB(A))	37	37	37	38	38	38