



6182S

Range :	6000 Series			
Function :	Multi-Temperatures Service			
Pack:	Premium			
Capacity:	I 82 Bottles**			



GENERAL FEATURES

	Full Glass door	Glass door	Solid door	
Gross weight packaged / net weight (kg)*	110 / 94	108 / 92	103 / 87	
Permitted ambient temperature range	12 – 30°C	12 – 35°C / 54 – 95°F		
Dimensions unpackaged н x W x D (mm)	1825 × 680 × 690			
Dimensions packaged H x W x D (mm)	1950 × 720 × 760			
Colour of body	Nero			

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 22°C
- · LED screen with touch buttons
- Electronic inner display and settings digital screen
- Temperature visualisation
- · Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production: • Air fan

• Compressor R600a/R134a Cords: CE/UK/JA/AU/CH/CN/US

Hot production: Heating element

Hot release: Automatic · Threshold: adjustable

Inner material: Aluminium

Exterior coating material: • HDF (High Density Fiber)

Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors: Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- · Charcoal filter (with meter)
- Front adjustable feet
- · Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Premium Pack: 14 sliding shelves ACMS

Capacity: 182 bottles**



OPTIONS PLUS



Lighting Atmosphere

A

lighting











Shelves

Equiped with a brake Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

Wiring	230V-50Hz			115V-60Hz		
Doors type	Solid	Glass	Full Glass	Solid	Glass	Full Glass
Energy efficiency rating	A+	Α	Α	1	1	1
Annual energy consumption Aec (kWh/year)***	128	165	165	183	256	256
Acoustic emissions (dB(A))	37	37	37	38	38	38





6182S

Range :	6000 Series			
Function :	Multi-Temperatures Service			
Pack:	Presentation			
Capacity:	I 62 Bottles**			



	Full Glass door	Glass door	Solid door	
Gross weight packaged / net weight (kg)*	110 / 94 108 / 92		103 / 87	
Permitted ambient temperature range	12 – 30°C	12 – 35°C / 54 – 95°F		
Dimensions unpackaged н x W x D (mm)	1825 × 680 × 690			
Dimensions packaged H x W x D (mm)	1950 x 720 x 760			
Colour of body	Nero			

TECHNICAL FEATURES

REGULATION

- Electronic regulation
- Temperature setting range from 5 to 22°C
- · LED screen with touch buttons
- Electronic inner display and settings digital screen
- Temperature visualisation
- · Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter)
- Automatic defrost

HOT - COLD - INSULATION TECHNOLOGIES

Cold production: • Air fan

• Compressor R600a/R134a Cords: CE/UK/JA/AU/CH/CN/US

Hot production: Heating element

Hot release: Automatic

· Threshold: adjustable

Inner material: Aluminium

Exterior coating material: • HDF (High Density Fiber)

Insulation type: • PU foam (59 mm)

EQUIPMENT & OPTIONS

EQUIPMENT

- 3 doors: Full Glass door, Glass door with black frame, Solid door
- Inner lighting: 2 LEDs (3 options: permanent, open door, disabled)
- · Charcoal filter (with meter)
- Front adjustable feet
- · Removable handle with centered lock
- · Humidity collector rearward

PACK OF SHELVES

Presentation Pack: 2 presentation kits AOPRESAR +

7 sliding shelves ACMS Capacity: 162 bottles**



OPTIONS PLUS







lighting







Shelves

Equiped with a brake Light wood or glossy black front Removable bottles identifiers + erasable felt-tip marker





A la carte options to upgrade the wine cabinet according to the needs.

ENERGY EFFICIENCY AND CONSUMPTION

Wiring	230V-50Hz			115V-60Hz		
Doors type	Solid	Glass	Full Glass	Solid	Glass	Full Glass
Energy efficiency rating	A+	Α	Α	1	1	/
Annual energy consumption Aec (kWh/year)***	128	165	165	183	256	256
Acoustic emissions (dB(A))	37	37	37	38	38	38