



9-6°C

A 2 temperatures multi-drinks cabinet, with an upper compartment dedicated to wine maturation, and a lower area to chill all kinds of drinks (Champagne, soft drinks, beers, fruit juices).



EAN Code: 3543290003803

Range : OXYGEN

Model : OXG2T206NVD

Fonction: Multi-drinks

Capacity\*: 206 Bottles\*\*

A constant temperature due to the dual Heating/Cooling controls.

Optin

Optimised humidity due to the circulation of humid air.



Air circulation ensured by a breather hole located inside the cellar.



No vibration thanks to the slow-cycles compressor fixed on silent blocs  $\pm$  evaporator flooded in the high density polyure thane foam.



Protection from UV light guaranteed with a glass door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

## Capacity: 206 bottles<sup>2</sup>

CONFIGURATION	Storage shelves	Sliding shelves	Beverage grid
Standard Configuration	5 (included one fixed)	I	1

## UNIVERSAL SHELF + REMOVABLE BEVERAGE GRID

Universal shelf: AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level: 12

**Material**: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



72 Bottles

« Storage»



« Sliding» 12 Bottles



« Presentation » 6 + 36 Bottles



Removable beverage grid

Artevino AOHUI shelf has a label holder :



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

- Standard configuration
- Traditional Bordeaux bottles
- Calculated with an ambient temperature of 25°C
- Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
- R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)
- 6 If the ambient temperature exceeds 25 ° C the performance of the wine cabinet may be altered. In this case, we recommend to set the temperature of the lower compartment at 6 ° C.

## **GENERAL FEATURES**

Gross weight, packaged(kg)  $^{\rm I}$  : 102 Net weight (kg)  $^{\rm I}$  : 86

Dimensions in packaging H x W x D (mm) :  $1950 \times 720 \times 760$ Dimensions H x W x D (mm) :  $1825 \times 680 \times 690$ 

Color scheme : Black

Energy efficiency rating : C

Acoustic emissions  $(dB(A))^5$  : 37

Electrical power  $(W)^3$  : 65

Electrical intensity  $(A)^3$  : 0.3

Consumption per 24h  $(KWh)^4$  : 0.74

Annual energy consumption  $AEc^*(kWh/year)^4$  : 271

Ambient temperature operating limit  $^6$  :  $12 - 25^{\circ}C$ 

- ✓ Digital electronic controls with 2 temperature settings :
  - √Upper compartment or ageing area: setting range from 10°C to 14°C.
  - √Lower compartment or beverage center: setting range from 3°C to 6°C.
- √ Temperature display on indoor sidewall
- ✓ Temperature fault alarm icon
- $\checkmark$  Interior lining of dimpled aluminium
- √ Removable beverage grid
- √ Glass door
- √ Reversible door
- √ Integrated handle into the door frame
- √ Lock
- √ 2 adjustable feet
- √ Storage grid in the low part

