



A multi-temperatures cabinet with a temperature staggering from 6°C to 20°C to serve your wines in the best possible conditions.



EAN Code : 3543290003353

| CONFIGURATION | Storage shelves | Sliding shelves | Capacity** |
|--------------------------------------|-----------------|-----------------|------------|
| Maximum Configuration (100% sliding) | - | 13 | 170 |
| Mixed Configuration | 2 | 4 | 206 |
| Minimum Configuration (100% storage) | 4 | 0 | 230 |
| Standard Configuration | 5 | - | 225 |

UNIVERSAL SHELF

Universal shelf : AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level : 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



« Storage »
72 Bottles



« Sliding »
12 Bottles



« Presentation »
6 + 36 Bottles

ArteVino AOHUI shelf has a label holder :



| Description | Reference | EAN Code |
|--|-----------|---------------|
| Single Solid beechwood universal shelf | AOHUI | 3543290002783 |

* Standard configuration

** Traditional Bordeaux bottles

*** Calculated with an ambient temperature of 25°C

**** Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration

***** R600a gas. With a R134a gas (for US, CA, Korea, Taiwan): 38 db(A)

| | |
|-------------|----------------------|
| Range : | OXYGEN |
| Model : | OXGMT225NPD |
| Fonction : | Service |
| Capacity* : | 225 Bottles** |



A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

| | |
|--|---------------------------|
| Gross weight, packaged(kg)* | : 101 |
| Net weight (kg)* | : 85 |
| Dimensions in packaging H x W x D (mm) | : 1940 x 700 x 750 |
| Dimensions H x W x D (mm) | : 1825 x 680 x 700 |
| Color scheme | : Black |

| | |
|--|--------------------|
| Energy efficiency rating | : A+ |
| Acoustic emissions (dB(A))***** | : 37 |
| Electrical power (W)*** | : 70 |
| Electrical intensity (A)*** | : 0.33 |
| Consumption per 24h (KWh) **** | : 0.35 |
| Annual energy consumption AEC* (kWh/year) **** | : 128 |
| Ambient temperature operating limit | : 12 - 30°C |

✓ **Digital electronic controls with temperature setting range from 6°C to 10°C (lower cabinet area) and 15°C to 20°C (upper cabinet area)**

✓ **Temperature display on indoor sidewall**

✓ **Double Hot/ Cold circuit > Automatic « Winter function »**

✓ **Temperature fault alarm icon**

✓ **Interior lining of dimpled aluminium**

✓ **Solid door**

✓ **Hygrometry ensured by the principle of thermodynamic pump**

✓ **2 adjustable feet**

✓ **Lock**

✓ **Storage grid in the low part**

✓ **Inox Handle**