






Code EAN: Available April 2021

Configuration



Bottles capacity with the standard configuration; 4 storing shelves: 230 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	13	170
Mixt Configuration	2	4	206
Standard Configuration	4	0	230

Oxygen

Range: Oxygen

Function: Ageing (1-temperature)

OXGIT230NVND Reference: Equipement: 4 storing shelves

230 Bottles* Capacity:



Homogenous constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1825 x 680 x 720**	Wei
Dimensions in pack (mm) :	1950 x 720 x 760	Wei
Colors:	Black	Wei
Door:	Glass door black frame	Use

Weight cabinet empty (kg) :	104
Weight equipped cabinet (kg) :	114,4
Weight in pack (kg) :	130,4
Useful volume (L) :	461

Equipment & Accessories

Equipment

- Glass door with black frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for bottles identification

Accessories

Universal shelves: AOHUI Code EAN: 3543290002783

Weight: 2,6 kg

Bottles capacity per level: 12* Material: Solid beech wood.

Modular system: you can choose the shelf configuration:






« 12 bottles » The label holder allows you to identify your bottle

quickly and easily



Presentation shelf « 6+22 bottles »



Storing shelf « 72 bottles »



Technical features

Control Panel

- Electronic regulation from 9°C to15°C; one identical temperature inside the wine
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production: Static cooling Hot production: Heating element

Ensure by the thermodynamical Humidity:

pump system Winter function: Automatic

R600a

Recommended temperature From 0°C to 30 °C range:

Aluminium Inner material: Insulation type: PU foam

Acoustic emissions (db(A)): 37 С Acoustical emission class: Consumption (kWh/year): 190 Energy efficiency rating: G

* Traditional Bordeaux bottles

** With the rear stop, without the handle