




EAN Code left hinge door: 3543290003841



EAN Code right hinge door: 3543290003650

Configuration



Bottles capacity with the standard configuration; 6 storing shelves:

7	7	D	U	LLI	62	•

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	9	163
Standard Configuration	3	3	199

Oxygen

Range: Oxygen

Function: Multi-functions (3-temperatures)

Model right hinge door: OXG3T199NPD Model left hinge door: OXG3T199NPG

Equipement: 6 shelves (3 storing shelves and 3 sliding shelves) and 2 compartments

Capacity: 199 Bottles*



Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our solid door with highly effective UV filter.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions $H \times W \times D$ (mm):	1825 × 680 × 725**
Dimensions in pack (mm):	1950 × 720 × 760
Colors:	Black
Door:	Solid door silver frame

Weight cabinet empty (kg) :	79
Weight equipped cabinet (kg) :	94,6
Weight in pack (kg) :	110,6
Useful volume (L) :	446

Equipment & Accessories

Equipment

- Solid black door with silver frame, stainless steel handle black or silver color
- Lock
- Left or right opening
- 2 adjustable feet
- Labels for the bottles identification
- 2 compartments in wood

Accessories

Universal shelves: AOHUI Code EAN: 3543290002783

Weight: 2,6 kg

Bottles capacity per level: 12* Material: Solid beech wood.

Modular system: you can choose the shelf configuration:



Sliding shelf « 12 bottles »

The label holder allows you to identify your bottle quickly and easily



Presentation shelf « 6+22 bottles »



Suitable to store all types



Storing shelf « 72 bottles »



Technical features

Control Panel

Electronic regulation from 10°C to 14°C for the middle part of the cabinet. From 15°C to 20°C for the highest part of the cabinet. The temperature of the lowest part of the wine cabinet is defined by the temperature setting of the middle part.

- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production: Static cooling Hot production: Heating element

Ensure by the thermodynamical Humidity:

pump system Winter function: Automatic R600a Gaz uses:

Recommended temperature From I2°C to 30°C

range: Aluminium Inner material: Insulation type: PU foam

Acoustic emissions (db(A)): 37 С Acoustical emission class: Consumption (kWh/year): 150 Energy efficiency rating: G

* Traditional Bordeaux bottles

** With the rear stop, without the handle