| ArteVir   | no                            |         | Multi-fu                 | unctions wir   | ne cabi | net with 3 isol  | ated compartments  |
|---|-------------------------------|---------|--------------------------|--|---------|--|--|
| FRANCE®   |                               |         |                          |  |         | O  | xygen  |
| CARANT  |                               |         |                          |  | Range   | :  | Oxygen   |
|   |                               |         |                          | (សំណ៍សំណ៍នាំណ<br>ឃើល(ដូ(សំណ៍ន)<br>- លែកសំណ៍ផ្លូ(ដូ(ដូ) | Funct   | ion :  | Multi-functions (3-temperatures)   |
|   |                               |         |                          | ପ୍ରିର୍ଣ୍ଣରାଜ<br>ପ୍ରିର୍ଣ୍ଣରାଜ<br>ଗ୍ରୋଚ୍ଚରାଜାନ           | Refer   | ence :   | OXM3T151NVND   |
|   |                               |         |                          |  | Equip   | ement :  | 4 shelves (2 storing shelves and 2 sliding shelves) and 2 compartments   |
| EAN Code : Availab                              | le April                      | 2021    |                          |  | Сарас   | ty :   | 151 Bottles*   |
|   | Bottles<br>configur<br>compar | ration; | ty with the<br>4 shelves | standard<br>and 2                                      |         | insulation, the cont<br>Humidity rate betw<br>design, the cooling<br>The natural ventii<br>constant air renewa | ble temperature thanks to the wine cabinet<br>croller and the aluminium walls.<br>ween 65% and 80% ensuring by our product<br>and venting system,<br>ng system of our wine cabinets ensures<br>al within the wine cabinet. |
| CONFIGURATION                                   | Stor<br>she                   | 0       | Sliding shelf            | Capacity*  |         | double pan reinford  | ainst UV rays thanks to our glass door with<br>ced with gaz argon to filter up to 97% of the   |
| Optimum Configuration<br>(100% sliding shelves) | -                             |         | 6                        | 137  |         |  | ks to the slow-cycles compressor fixed on  |
| Standard Configuration                          | 2                             | !       | 2                        | 151  |         | silentblocs + eva<br>polyurethane foam.  | aporator flooded in the high density   |

| General realures                       |                        |                                |       |  |  |  |  |
|--|------------------------|--------------------------------|-------|--|--|--|--|
| Dimensions $H \times W \times D$ (mm): | 1480 x 680 x 720**     | Weight cabinet empty (kg) :    | 81    |  |  |  |  |
| Dimensions in pack (mm) :              | 1605 x 720 x 760       | Weight equipped cabinet (kg) : | 88,8  |  |  |  |  |
| Colors :                               | Black                  | Weight in pack (kg) :          | 103,8 |  |  |  |  |
| Door:                                  | Glass door black frame | Useful volume (L) :            | 346   |  |  |  |  |

# **Equipment & Accessories**

#### Equipment

•

- Glass door with black frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
  Reversible door
  2 adjustable feet
  - Labels for the bottles identification

#### Accessories

#### Universal shelves: AOHUI Code EAN : 3543290002783

Weight : 2,6 kg

Pottlos conscitu - ----

Bottles capacity per level : 12\* Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf **« 12 bottles »** The label holder allows you to identify your bottle quickly and easily



Suitable to

of bottles

store all types



Storing shelf **« 72 bottles** :

« 72 bottles »



**Technical features** 

### Control Panel

- Electronic regulation from  $10^{\circ}$ C to  $14^{\circ}$ C for the middle part of the cabinet. From  $15^{\circ}$ C to  $20^{\circ}$ C for the highest part of the cabinet. The temperature of the lowest part of the wine cabinet is defined by the temperature setting of the middle part.
- Inner electronic display, Red Leds screen
  Visual alarm for the
- temperature fault
- Temperature display

\*\* With the rear stop, without the handle

Automatic Winter function

## Performances

| Cold production :           | Static cooling                               |  |  |
|-----------------------------|--|--|--|
| Hot production :            | Heating element                              |  |  |
| Humidity:                   | Ensure by the thermodynamical<br>pump system |  |  |
| Winter function:            | Automatic                                    |  |  |
| Gaz uses :                  | R600a  |  |  |
| Recommended temperature     | From I2°C to 30 °C                           |  |  |
| range :                     |  |  |  |
| Inner material:             | Aluminium                                    |  |  |
| Insulation type:            | PU foam                                      |  |  |
| Acoustic emissions (db(A)): | 37   |  |  |
| Acoustical emission class : | С  |  |  |
| Consumption (kWh/year) :    | 150  |  |  |
| Energy efficiency rating :  | G  |  |  |
| *                           | Traditional Bordeaux bottles                 |  |  |