




**EAN Code : 3543290003735**

## Configuration



Bottles capacity with the standard configuration; 4 storing shelves :  
**177 Bottles\***

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	10	141
Mixt Configuration	2	1	177
Standard Configuration	4	0	177

# Oxygen

Range :	Oxygen
Function :	Serving (multi-temperatures)
Model :	OXMMT177NVSD
Equipement :	4 storing shelves
Capacity :	177 Bottles*



Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

## General Features

Dimensions H x W x D (mm):	1480 x 680 x 720**
Dimensions in pack (mm):	1605 x 720 x 760
Colors :	Black
Door:	Glass door silver frame

Weight cabinet empty (kg) :	74
Weight equipped cabinet (kg) :	84,4
Weight in pack (kg) :	99,4
Useful volume (L) :	360

## Equipment & Accessories

### Equipment

- Glass door with silver frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for the bottles identification

### Accessories

**Universal shelves: AOHUI**

**Code EAN : 3543290002783**

**Weight : 2,6 kg**

**Bottles capacity per level : 12\***

**Material : Solid beech wood.**

Modular system : you can choose the shelf configuration :



Sliding shelf  
« 12 bottles »



Presentation shelf  
« 6+22 bottles »



Storing shelf  
« 72 bottles »

The label holder allows you to identify your bottle quickly and easily



Suitable to store all types of bottles



## Technical features

### Control Panel

- Electronic regulation from 6°C to 20°C; From 6°C to 10°C for the lowest part of the cabinet and from 15°C to 20°C for the highest part of the cabinet
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

### Performances

Cold production :	Static cooling
Hot production :	Heating element
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 12°C to 30 °C
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Acoustical emission class :	C
Consumption (kWh/year) :	161
Energy efficiency rating :	G

\* Traditional Bordeaux bottles

\*\* With the rear stop, without the handle