




EAN Code : 3543290003728

Configuration



Bottles capacity with the standard configuration; 4 storing shelves :
177 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	9	122
Mixt Configuration	2	1	177
Standard Configuration	4	0	177

Oxygen

Range :	Oxygen
Function :	Serving (multi-temperatures)
Model :	OXMMT177NPD
Equipement :	4 storing shelves
Capacity :	177 Bottles*



Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our solid door with highly effective UV filter.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1480 x 680 x 725**
Dimensions in pack (mm):	1605 x 720 x 760
Colors :	Black
Door:	Solid door silver frame

Weight cabinet empty (kg) :	63
Weight equipped cabinet (kg) :	73,4
Weight in pack (kg) :	88,4
Useful volume (L) :	360

Equipment & Accessories

Equipment

- Solid black door with silver frame, stainless steel handle,
- Lock
- 2 adjustable feet
- Labels for the bottles identification

Accessories

Universal shelves: AOHUI

Code EAN : 3543290002783

Weight : 2,6 kg

Bottles capacity per level : 12*

Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »

The label holder allows you to identify your bottle quickly and easily



Presentation shelf
« 6+22 bottles »



Suitable to store all types of bottles



Storing shelf
« 72 bottles »



Technical features

Control Panel

- Electronic regulation from 6°C to 20°C; From 6°C to 10°C for the lowest part of the cabinet and from 15°C to 20°C for the highest part of the cabinet
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production :	Static cooling
Hot production :	Heating element
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 12°C to 30 °C
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Acoustical emission class :	C
Consumption (kWh/year) :	125
Energy efficiency rating :	F

* Traditional Bordeaux bottles

** With the rear stop, without the handle