





EAN Code: Available April 2021

Configuration



Bottles capacity with the standard configuration; 2 shelves: 98 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	5	74
Standard Configuration	1	1	98

Dxygen

Range: Oxygen

Function: Ageing (1-temperature)

OXPIT98NVND Model:

Equipement: 2 Shelves (I storing shelf and I sliding shelf)

98 Bottles* Capacity:

Homogenous constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.

Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,

The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.

Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.

No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	960 × 680 × 720**	Weight cabinet empty (kg) :	52
Dimensions in pack (mm) :	1090 x 720 x 760	Weight equipped cabinet (kg) :	57,2
Colors:	Black	Weight in pack (kg) :	70,2
Door:	Glass door silver frame	Useful volume (L) :	209

Equipment & Accessories

Equipment

- Glass door with black frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for bottles identification

Accessories

Universal shelves: AOHUI Code EAN: 3543290002783

Weight: 2,6 kg

Bottles capacity per level: 12* Material: Solid beech wood.

Modular system: you can choose the shelf configuration:






« 12 bottles » The label holder

allows you to identify your bottle quickly and easily



Presentation shelf







Storing shelf « 72 bottles »



Technical features

Electronic regulation from 9°C to15°C; one identical temperature inside the wine

Inner electronic display, Red Leds screen

- **Control Panel** Visual alarm
 - temperature fault Temperature display
 - Automatic Winter function

for

the

Performances

Cold production: Static cooling Hot production: Heating element

Ensure by the thermodynamical Humidity:

pump system Winter function: Automatic R600a Gaz uses:

Recommended temperature From 0°C to 30 °C

range: Aluminium Inner material: Insulation type: PU foam

Acoustic emissions (db(A)): 37 С Acoustical emission class: Consumption (kWh/year): 128 Energy efficiency rating: G

* Traditional Bordeaux bottles

** With the rear stop, without the handle